
## 60" x 32" x 17"

Citti® is derived from sanskrit for "free spirit." At the same time, the name evokes today's great cities: these are the perfect baths for urban living.



DESCRIPTION	тми	TUB	
Left	BC7DRA0LT-XX	BC7DRA0LN-XX	
Right	BC7DRA0RT-XX	BC7DRA0RN-XX	

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$
Jets	42
1 heated backrest	Included
Mia® Control	Included
Geysair®	Included
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$

<b>TUB</b> Soaker	\$
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy

FEATURES				
Installation type		Alcove (3 walls)		
Integrated skirt & tile flange (specify right or left)		Installed & Included		
No. of bathers	•	Imp. gallo	ns	37
US gallons	45			
INTEGRATED WASTE & OVERFLOW BOVERINI-XX				
White 01, Biscuit 02, Chrome 07, Brushed Nickel 09, Polished Nickel 10		Installed & Included		
STANDARD COLOR				
White 01 Biscuit 02				Included

OPTIONS (UPCHARGE APPLICABLE)		
COLOR		
Gray 05	\$	
FINISH		
UltraVelour Matte Finish (White only) BVEL	\$	
INTEGRATED WASTE & OVERFLOW BOVERINI-XX		
Matte Black 19, Black Chrome 12, Satin Brass 18	\$	
CONTROL (TMU only)		
MiaPlus®* BMIAPI2-XX or BMIAP2-XX	\$	
MiaMulti® BMIAM1-XX	\$	
IF REQUIRED BY CONSTRUCTION CODE OR INSTALLED WITH ITD		
Brass waste & overflow kit BDRCOB	\$	
Brass waste kit BDRCB	\$	

Turbine must be remotely installed. With the AromaCloud® and/or Control on the deck, a complete shower door cannot be installed.

Don't forget to specify the **finish of the integrated waste & overflow.**\* The MiaPlus® Control is included when purchasing Chromatherapy

on a TMU.

**TOTAL PRICE** 







K



Ideal for making the most of a small space by turning it into a place to experience multiple therapeutic experiences.

## INSTALLATION





LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	10 7/8"
В	Outside edge to centre of waste hole	2 3/4"
С	Total length	60"
D	Total width	32"
E	Bathing well length	49 1/4"
F	Bathing well width	21 1/8"
G	Deck width	3 3/4"
н	Deck width at waste end	2"
ı	Height from bottom of tub to top deck	17"
J	Height from drain to center of overflow	14 1/2"
К	Slope of backrest	17°
L	Deck width overflow side	2 1/8"

- A AromaCloud® position
- **●** Control position when factory-installed (Mia® or DOT)
- Indicates heated backrest (TMU)
- Indicates WarmTouchShell® position (TUB)

TECHNICAL SPECIFICATIONS		
Hot water	Should be 70% of water capacity of TUB or greater.	Approx. shipp
supply required	, , ,	Turbine power
Turbine dedic	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A. 120 V, 60 hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option</b> , a <b>second line is needed 15 A. 120 V, 60 hz</b> , dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater
		WARRANTY
Others  - The turbine must be remotely installed Citti bathtubs include an integrated tile flange, specify right or le	- The turbine must be <b>remotely installed</b>	Controls-LED-0
	- Citti bathtubs include an integrated tile flange, specify right or left.	Bath & turbine
	st be installed by certified professionals only and according to our Owner's Manual as well as federal, and local building codes and regulations (www.bainultra.com/documentation/documentation).	* Some restrictions

Approx. shipping weight	125 lbs
Turbine power	550 W
Air heater	600 W
WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

<sup>\*</sup> Some restrictions apply | www.bainultra.com/warranty





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.