PRODUCT SHEET

NEW

IBE OVAL 5830

58" x 30" x 21" (FREESTANDING)

Vibe is a new collection of therapeutic bathtubs with minimalist and contemporary flair. The collection is perfect for urban city dwellers who want to bring value and refinement to smaller bathrooms.

PRODUCT NO.

DESCRIPTION	тми	тив
Freestanding	BVIAOF00T-XX	BVIAOF00N-XX
THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system		\$
Jets		35
1 heated backrest		Included
MiaPlus [®] Control*		Included
Geysair®		Included
Illuzio Chromatherapy BCHRO6		\$
TUB Soaker		\$
Illuzio Chromatherapy BCHRO6		\$
WarmTouchShell® BWTS		\$
DOT control		Included with therapy
FEATURES		
Installation type		Freestanding

Installation type			F	reestanding
No. of bathers	*	Imp. gallo	ns	34
US gallons	40			
INTEGRATED WASTE & O	VERFLO		xx	
White 01, Chrome 07, Brush Polished Nickel 10	White 01, Chrome 07, Brushed Nickel 09, Polished Nickel 10		Installed & Included	
STANDARD COLOR				
White 01				Included

OPTIONS (UPCHARGE APPLICABLE) COLOR \$ Black / White 66 NEW FINISH \$ UltraVelour Matte Finish (White only) BVEL **INTEGRATED WASTE & OVERFLOW BOVERINI-XX** Matte Black 19, Black Chrome 12, Satin Brass 18 \$ **ISLAND TUB DRAIN™**** Island Tub Drain[™] BISLDD \$ Cast Iron Island Tub Drain[™] BISLDDCI \$ CONTROL MiaMulti® BMIAM2-XX \$ IF REQUIRED BY CONSTRUCTION CODE OR INSTALLED WITH ITD \$ Brass waste & overflow kit BDRCOB Brass waste kit BDRCB \$

Don't forget to specify the **finish of the integrated waste & overflow.** * Control must be wall-mounted. Faucets must be freestanding or wall-mounted. ** An Island Tub Drain™ is required when there is **no access under the bath**.

TOTAL PRICE

\$









VIBE OVAL 5830 (FREESTANDING)

INSTALLATION





LETTER	DESCRIPTION	MEASURE
Α	Total length	58"
в	Total width	30"
с	Bathing well length	41 1/4"
D	Bathing well width	20 1/8″
E	Deck width	1 3/8"
F	Deck width at headrest	1 3/8″
G	Center waste to air intake	3 1/2"
н	Total height	21″
I	Maximum water level	14 3/8"
J	Slope of backrest	26°
к	Base length	47"
L	Base width	24 1/4"

Indicates heated backrest (TMU)

(indicates WarmTouchShell® position (TUB)

Hot water supply required	Should be 70% of water capacity of TUB or greater.	
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option , a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	

Others	 Faucet must be freestanding or wall-mounted. The turbine must be remotely installed. Controls cannot be installed on the deck of the bath.
Our products pour	t be installed by certified professionals only and according to our C

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

Cutting template	# 90000080
Approx. shipping weight	225 lbs
Turbine power	550 W
Air heater	600 W
WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years
* Some restrictions apply I www.bain	ultra.com/warranty

* Some restrictions apply | www.bainultra.com/warranty



TECHNICAL SPECIFICATIONS

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.