KALLISTA

Pressure-Balancing Valve with Diverter

FEATURES

- Brass valve body
- Pressure-balancing diaphragm design valve
- One-piece diaphragm cartridge design for ease of maintenance
- Mixing valve cycles from "cold " to "hot "
- Integral diverter mechanism
- High-temperature limit setting for added safety
- Available with or without screwdriver stops
- Designed for showerhead and handshower applications

CODES/STANDARDS APPLICABLE

P29305

• ASME A112.18.1/CSA B125.1

• ASSE 1016

1/2"- 14 NPT OD 5/8" ID 5-3/4" (146 mm) for 1/2" Nom. Copper Tubing (all Inlet & Outlet Ports) With Stops Secondary Outlet Port 2-1/16" 4" (102 mm) Valve diverts to this port. (52 mm) Without Stops 2" (51 mm) 3-13/16" 1/2" Hot 1/2" Cold (90 mm) THING Min **Finished Wall** 2-3/4" (70 mm) Primary Outlet Port Max 3-1/2" (89 mm) **Finished Wall**

Valve defaults to this port.

ROUGHING-IN NOTES

Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet

SPECIFIED MODEL		
Model	Description	Finishes
P29305-00	Pressure-Balancing Valve with Diverter, without screwdriver stops	D NA
P29305-WS	Pressure-Balancing Valve with Diverter, with screwdriver stops	🗅 NA

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.

Questions? Problems? For additional assistance, please contact KALLISTA's Customer Service Department at 1-888-4-KALLISTA (1-888-452-5547) or FAX 1-888-272-3094.

Specified model meets or exceeds the following: